



VENABLES OAK

FLOORING

Oak flooring is produced from kiln dried material. It is machined with tongued and grooved edges and has stress relieving grooves to the underside to keep it flat. The boards are end matched and are easy to lay. They are available in 21mm thickness and in 120, 140, 160, 180, and 200mm finished face widths and in random lengths of 1.0m to 2.5m long. Venables Oak also supplies OSMO floor wax and other finishing products and can help you select the best for your application.

We are also able to machine floors to individual specifications.

When laying solid wooden flooring, it is essential to make sure that the whole area is thoroughly dried out, sealed from the elements, and that all wet building trades have been completed. If the room or building has recently had wet trades we recommend the use of a dehumidifier to dry out the environment before the flooring is introduced. Once installed, we recommend leaving the flooring in the room for approximately a week to settle.

Clients are welcome to visit to discuss exact requirements. And for those who are not sure of the exact requirements, there is an equally warm welcome and the knowledge and time to help you choose the best floor for your application.



Character grade European oak flooring

k t: 01630 661775

f: 01630 661707

Venables Brothers Ltd
Chipnall Sawmill,
Cheswardine,
Market Drayton,
Shropshire TF9 2RB

www.venablesoak.co.uk

VENABLES OAK



Oak garden room, Shropshire



Oak flooring and skirting

FLOORING



Oak flooring and four panel doors



Oak flooring, doors, skirting, arch and staircase, Henley

t: 01630 661775 f: 01630 661707

Venables Brothers Ltd
Chipnall Sawmill, Cheswardine,
Market Drayton, Shropshire TF9 2RB

www.venablesoak.co.uk